














SCAPA NORTH AMERICA INDUSTRIAL TAPE PRODUCTS











Product #	Description/ Available Colors	Features	Uses	Tensile Strength (lb./in.)	Peel Adhesion (oz/in)	Total Thickness (mils)*
POLYETHYLENE COATED CLOTH TAPES						
441	Economy-Grade Duct Tape 	High adhesion over a wide temperature range. Easily torn by hand. Superior adhesion to poly films. Natural rubber adhesive.	Light packaging. Temporary holding. Mending and sealing. Color coding.	22	50	7
442	Utility-Grade Duct Tape 	High adhesion over a wide temperature range. Easily torn by hand. Superior adhesion to poly films. Natural rubber adhesive.	Light packaging. Temporary holding. Mending and sealing. Color coding.	22	50	8.5
443	Contractor-Grade Duct Tape 	High adhesion over a wide temperature range. Easily torn by hand. Superior adhesion to poly films. Natural rubber adhesive.	Abatement. Seaming sheet metal and flex duct. Temporary holding. Light packaging. Mending and sealing.	22	50	9
445	Multi-Purpose Duct Tape 	High adhesion. Easily torn by hand.	Seaming sheet metal and flex duct. General industrial maintenance.	22	50	10
448	Industrial-Grade Duct Tape 	Aggressive high-performance natural rubber adhesive.	Heavy-duty abatement and sealing applications.	32	60	11
446	Professional-Grade Duct Tape 	High-tack natural rubber adhesive. Extra-strength cloth. Easily torn by hand.	Heavy-duty sealing of ductwork seams and joints.	35	70	13
145	Super-Heavy-Duty Duct Tape 	Excellent adhesion. Extra-strength cloth. Easy unwind. Natural rubber adhesive.	Sealing of ductwork seams and joints in demanding applications.	40	75	17
5241	Commercial-Grade Duct Tape 	Natural rubber adhesive. Easy unwind. Straight tear.	Seaming sheet metal and flex duct. Temporary holding. Light packaging. Mending and sealing.	28	50	10.5
COTTON CLOTH TAPES						
164	Single Coated Cloth Tape 	Uniform unwind. Easily torn by hand with good conformability. Meets Chrysler MS-CH 62 specification. Natural rubber adhesive.	Automotive and appliance wire harness applications.	35	35	9
169	Flame-Retardant Cloth Tape 	Flame-retardant backing and adhesive. Meets Ford specification ESB-M3G71. Meets Delphi specification ES-M-2386. Fire-retardant natural rubber adhesive.	Automotive and appliance wire harness applications requiring a flame-retardant tape.	40	32	9.5
175 (Natural) 176 (Black)	Single Coated Cloth Tape	Excellent abrasion resistance. Leaves no residue upon removal. Good conformability. Natural rubber adhesive.	Wire marking. Color coding. General industrial assembly.	35	30	10/9.5
VINYL COATED CLOTH TAPES						
125	Matte-Finish Gaffer's Tape 	Natural rubber adhesive provides high tack. High tensile strength. Easy unwind.	Printable gaffer's tape.	48	28	11
225	Premium Matte-Finish Gaffer's Tape 	Temperature-resistant natural rubber adhesive provides high tack and clean removal. High tensile strength.	Premium printable gaffer's tape.	45	50	12
228	Flame-Retardant Gaffer's Tape 	Fire retardant natural rubber adhesive.	Flame-retardant gaffer's tape.	48	30	11

*Total thickness excludes liner. All Polyflex products are available on plastic cores for use in clean room environments.

Colors shown are representations only and are not exact matches of the colors offered. Custom colors can be produced but up-charges, minimum order quantities and extended lead times may apply. Consult your Account Executive.



SCAPA NORTH AMERICA INDUSTRIAL TAPE PRODUCTS

Product #	Description/ Available Colors	Features	Uses	Tensile Strength (lb./in.)	Peel Adhesion (oz/in)	Total Thickness (mils)*
DOUBLE COATED CLOTH TAPES						
174	Double Coated Cloth Tape PE Liner	Aggressive natural rubber adhesive leaves no residue upon removal. Good shear strength.	Plate mounting. Carpet installation. Temporary holding.	40	50	13
274	Double Coated Cloth Tape Easy-release PE Liner	Aggressive natural rubber adhesive leaves no residue upon removal. Good shear strength.	Convention carpet installation.	30	40/50	12
POLYFLEX® POLYETHYLENE TAPES						
130	Polyethylene Film Tape 	Synthetic rubber adhesive provides low adhesion and allows for low-residue removal. Easily torn by hand with good conformability.	Surface protection.	20	25	7
133	Heavy-Duty Polyethylene Film Tape 	Aggressive synthetic rubber adhesive. Excellent low-temperature bonding. Serrated edge for easy tearing.	Surface protection. Polyethylene splicing.	24	60	7.5
135	Polyethylene Film Tape 	Synthetic rubber adhesive provides high adhesion across a range of temperatures. Very good conformability and clean removal.	Surface protection. Polyethylene splicing. Wire identification.	18	60	7
136	Polyethylene Film Tape 	Synthetic rubber adhesive provides high adhesion across a range of temperatures. Very good conformability and clean removal.	Surface protection. Polyethylene splicing. Wire identification.	22	70	9
139	Heavy-Duty Polyethylene Film Tape 	Synthetic rubber adhesive provides high adhesion across a range of temperatures. Clean removal.	Heavy-duty abatement. Surface protection. Polyethylene splicing. Wire identification.	24	40	7.5
POLYFLEX® UV-RESISTANT POLYETHYLENE TAPES						
134	Polyethylene Film Tape 	Conformable heavy-duty backing. Short-term UV-resistance. Synthetic rubber adhesive. No residue upon removal.	Premium stucco masking. Greenhouse repair.	22	70	9
234	Polyethylene Film Tape 	Conformable heavy-duty backing. Short-term UV-resistance. Synthetic rubber adhesive. No residue upon removal.	Premium stucco masking. Greenhouse repair.	18	60	7
533	Polyethylene Film Tape 	30-90 day UV- resistance. Bonds to a variety of substrates. Synthetic rubber adhesive. Clean removal.	Premium stucco masking. Greenhouse repair.	22	60	7
433	Polyethylene Film Tape 	Long-term UV- resistance. Bonds to a variety of substrates. Synthetic rubber adhesive. Clean removal.	Premium stucco masking. Greenhouse repair.	22	65	7
434	Heavy-Duty Polyethylene Film Tape 	Long-term UV- resistance. Bonds to a variety of substrates. Synthetic rubber adhesive. Clean removal.	Preservation sealing. Premium stucco masking. Greenhouse repair.	25	75	9

*Total thickness excludes liner. All Polyflex products are available on plastic cores for use in clean room environments.

Colors shown are representations only and are not exact matches of the colors offered. Custom colors can be produced but up-charges, minimum order quantities and extended lead times may apply. Consult your Account Executive.



North American Headquarters
111 Great Pond Drive
Windsor, CT 06095
(860) 688-8000
FAX (860) 688-7000

ISO 9001:2000
CERTIFICATE #0000778
CERTIFICATE #024847

800-653-5316
www.scapana.com
appsupport@scapana.com