

Go for the Gold...

Renfrew **CMP Gold™** Premium Hockey Tape

CMP Gold Premium Hockey Tape is specifically designed for today's composite hockey sticks. The new adhesive formulation and polyester/cotton blended cloth used on CMP Gold results in a "beefier" product that has been specially formulated to stick to the surface of composite stick blades, while improving performance and durability. CMP Gold can also be used on traditional wood or wood/fiberglass sticks with the same quality performance.

- Premium polyester/cotton cloth tape designed specifically for today's composite hockey sticks
- New adhesive formulation results in a "beefier" cloth tape with increased wear characteristics
- Stays on the stick longer than traditional cloth tapes
- Requires less frequent taping



“Renfrew CMP Gold is a great product! The added cushion that this tape provides results in better feel and improved puck control. When it comes to quality hockey tapes, Renfrew Hockey Tape products are second to none.”

*Steve Yzerman
Three-time Stanley Cup Champion*

RENFREW
HOCKEY TAPE

For more information, contact us at:

1-800-542-9715

hockeyorders@scapana.com
www.renfrewhockeytape.com

CMP Gold™ 104

Available Patterns & Colors

Patterns

- USA and Canadian Flags
- Team Canada
- Flames
- Skull and Cross-bones
- Breast Cancer Ribbon
- Camouflage: Olive, Pink, Blue and Orange



Solid Colors

- Burgundy
- Plum
- Red
- Orange
- Yellow
- Green
- Teal Blue
- Royal Blue
- Navy Blue
- Black
- White
- Bubble Gum Pink
- Neon Orange
- Neon Green
- Neon Pink



Technical Data

TECHNICAL PROPERTIES

| | |
|--|---------------------|
| Total Thickness (not including liner) | 10.0 mils (.254mm) |
| Adhesive Thickness (rubber) | 3.75 mils (.095 mm) |

ADHESIVE TEST DATA

| | | |
|--|------------------|-----------------|
| Peel Adhesion (PSTC 101 Mod./180°) | <u>Oz./Inch</u> | <u>(N/25mm)</u> |
| Initial to S.S. (20 min. @ RT) | 28 | 7.7 |
| Backing Adhesion (PSTC 101 Mod./180°) | | |
| Initial to Backing Substrate (20 min. @ RT) | 20 | 5.5 |
| Tensile Strength (ASTM D-1000) | <u>lbs./Inch</u> | <u>(N/25mm)</u> |
| | 35 | 153 |

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. **THE PRODUCTS DISCUSSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED.** No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.